

CERTIFICATE OF CONSTANCY OF PERFORMANCE

1239/CPR/0822101

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products, it's certified that the

Construction product: **Glass in building. Laminated glass and laminated safety glass**

Scope of Certification:
(references) **LAMISSOL PRESERVE**

References included in the scope of the certification are listed in the annex of this certificate

Provided and produced by: **ASTIGLASS, S.L.**
P.I. La Campiña Fase IV
C/Dehesa de las Yeguas, 1
41400 - ECIJA (Sevilla)

Is subject to a factory production control and to the inspection of samples in accordance to a prescribed test plan by the manufacturer, and that the Notified Body TECNALIA R&I CERTIFICACION S.L. has carried out initial type tests for all relevant characteristics of the product, as well as the initial inspection of the factory and FPC, and the continuous surveillance, assessment and approval of FPC

This certificate shows compliance with all regulations applicable to the conformity assessment in the Annex ZA of the standard

EN 14449:2005+/AC:2005

and that the product meets the minimum requirements applicable.

System of assessment and verification of constancy of performance : SYSTEM 1



Issued on: 05/04/2017
Last modified on: 08/06/2020
Expires on: 13/08/2023
Serial no: 082210103-E

05/04/2017
08/06/2020
13/08/2023



Carlos Nazabal Alsua
Manager

This document allows the manufacturer to fix the CE mark.

This certificate may be modified, temporarily suspended and withdrawn by TECNALIA R&I CERTIFICACION.

The validity of this certificate can be through consultation in www.tecnaliacertificacion.com.

ANNEX
CERTIFICATE OF CONSTANCY OF PERFORMANCE
1239/CPR/0822101

Construction product:

Bullet resistant laminated safety glass

References	Description
22.4 BR1	Bullet resistance class: BR1/NS Basic soda lime silicate float glass with PVB layers Nominal thickness: 24,5 mm
18.10 BR2	Bullet resistance class: BR2/S Basic soda lime silicate float glass with PVB layers Nominal thickness: 21,8 mm
36.12 BR4	Bullet resistance class: BR4/S Basic soda lime silicate float glass with PVB layers Nominal thickness: 40,6 mm